

Gear BU+ 8000: is a paste with a high content of Teflon which offers maximum lubrication and anti-wear protection to the gear and bearing surfaces of all types of gears (helical, spur and worm drive).

Gear BUSL 8050: Treatment of leaking transmission systems using bio unsaturated oil type lubricant and where the leakage is below 20 ltrs per day

Gear BUSLL 8080: Treatment of leaking transmission systems using bio unsaturated oil type lubricant and where the leakage is 20 – 50 ltrs per day

Gear BUSLLL 8090: Treatment of leaking transmission systems using bio unsaturated oil type lubricant and where the leakage is above 50 ltrs per day

STERN TUBE BU+ 8100: is an additive, which when added to existing lube oil, improves the load bearing capability, which results in less wear under all operating conditions.

STERN TUBE BUSL 8200: Treatment of leaking stern tube systems using bio unsaturated oil type lubricant where the leakage is below 15 ltrs per day

STERN TUBE BUSLL 8300: Treatment of leaking stern tube systems using bio unsaturated oil type lubricant where the leakage is from 15 to 50 ltrs per day

STERN TUBE BUSLLL 8390: Treatment of leaking stern tube systems using bio unsaturated oil type lubricant where the leakage is above 50 ltrs per day

STERN TUBE BUCSL 8400: Treatment of leaking stern tube systems - Face seal/Cedervall using bio unsaturated type lubricant and where the leakage is below 50 ltrs per day

THRUSTER BU+ 8600: Used as start- up lubrication for all types of thruster bearings and seals. Used as an additive in existing Hydraulic Oil to reduce the risk of leakage.

THRUSTER BUSL 8700: An additive where the leakage is 0.5 to 1.0 ltrs per hour of operation and a filter size of 40-microns is acceptable.

THRUSTER BUSLL 8800: An additive where the leakage is 1.0 to 2.0 ltrs per hour of operation and a filter size of 40-microns is acceptable.

THRUSTER BUSLLL 8090: An additive where the leakage over 2.0 ltrs per hour of operation and a filter size of 40-microns is acceptable.

THRUSTER GEAR BUG+ 8900: Is a paste with a high content of Teflon which offers maximum lubrication and anti-wear protection to the gear and bearing surfaces of all types of gears (helical, spur and worm drive).

THRUSTER GEAR BUGSL 8950: Leaking transmission systems using bio unsaturated oil type lubricant and where the leakage is below 20 ltrs per day

THRUSTER GEAR BUGSLL 8950: Leaking transmission systems using bio unsaturated oil type lubricant and where the leakage is 20 – 50 ltrs per day

THRUSTER GEAR BUGSLLL 8990: Leaking transmission systems using bio unsaturated oil type lubricant and where the leakage is above 50 ltrs per day

HYDRAULICS BU+ 8500: is an additive for treatment of systems containing bio unsaturated hydraulic oils as carrier.

HYDRAULICS BUSL 8550: Leaking hydraulic systems where the leakage is below 12 ltrs per day or 0.5 ltrs per hour.

HYDRAULICS BUSLL 8580: Leaking hydraulic systems where the leakage is above 24 ltrs per day or 1 ltr per hour

ABCON AS

Ved Kladebo 9
DK-2970 Horsholm
DENMARK

Master Distributor/ Agent /Distributeur : North America

VapCor Inc.

530 Eastchester Ave. St. Catharines, Ontario, Canada, L2M 7P3,
Seattle, Washington, Miami Florida, USA

Ph# 905-346-2638 Ph# 866-642-1311, Fax# 905-682-3300

Solutions@Vapcor.com www.vapcor.com

info@abcon.eu

www.abcon.eu

TEL: +45 45161163

VAT No DK10025753