

Gear+ 7000: is a paste with a high content of Teflon which offers maximum lubrication and anti-gear protection to the gear and bearing surfaces of all types of gears (helical, spur and worm drive).

Gear SL 7050: Treatment of leaking transmission systems using Mineral oil type lubricant and where the leakage is below 20 ltrs per day

Gear SLL 7080: Treatment of leaking transmission systems using Mineral oil type lubricant and where the leakage is 20 – 50 ltrs per day

STERNTUBE+ 7100: is an additive, which when added to existing lube oil, improves the load bearing capability, which results in less wear under all operating conditions.

STERN TUBE SL 7200: Treatment of leaking stern tube systems using Mineral oil type lubricant where the leakage is below 15 ltrs per day

STERN TUBE SLL 7300: Treatment of leaking stern tube systems using Mineral oil type lubricant where the leakage is from 15 to 50 ltrs per day

STERN TUBE SLLL 7390: Treatment of leaking stern tube systems using Mineral oil type lubricant where the leakage is above 50 ltrs per day

STERN TUBE CSL 7400: Treatment of leaking stern tube systems - Face seal/Cedervall using Mineral Oil type lubricant and where the leakage is below 50 ltrs per day

THRUSTER+ 7600: Used as start- up lubrication for all types of thruster bearings and seals. Used as an additive in existing Hydraulic Oil to reduce the risk of leakage.

THRUSTER SL 7700: An additive where the leakage is 0.5 to 1.0 ltrs per hour of operation and a filter size of 40-microns is acceptable.

THRUSTER SLL 7800: An additive where the leakage is 1.0 to 2.0 ltrs per hour of operation and a filter size of 40-microns is acceptable.

THRUSTER SLLL: An additive where the leakage over 2.0 ltrs per hour of operation and a filter size of 40-microns is acceptable

THRUSTER GEAR G+ 7900: is a paste with a high content of Teflon which offers maximum lubrication and anti-wear protection to the gear and bearing surfaces of all types of gears (helical, spur and worm drive).

THRUSTER GEAR GSL 7950: Leaking transmission systems using Mineral oil type lubricant and where the leakage is below 20 ltrs per day

THRUSTER GEAR GSLL 7980: Leaking transmission systems using Mineral oil type lubricant and where the leakage is 20 – 50 ltrs per day

THRUSTER GEAR GSLLL 7990: Leaking transmission systems using Mineral oil type lubricant and where the leakage is above 50 ltrs per day

HYDRAULICS + 7500: is an additive for treatment of systems containing hydraulic oils as carrier.

HYDRAULICS SL 7550: Leaking hydraulic systems where the leakage is below 12 ltrs per day or 0.5 ltrs per hour.

HYDRAULICS SLL 7580: Leaking hydraulic systems where the leakage is above 24 ltrs per day or 1 ltr per hour