





ANTICORROSION TAPE SYSTEM

PetroWrap® Anti-Corrosion Tape Systems provides a superior way to protect your deck equipment, hydraulics, steel pipes, flanges, valves, marine pilings and structures, or any other equipment, from the effects of corrosion. Composed mainly of petrolatum and specific anti-corrosion agents, **PetroWrap®** Tape Products are formulated to provide economical long-term protection from water, salt, alkalis, and acids and require no maintenance.

PetroWrap® are made from non-woven stitch-bonded synthetic fabric, fully impregnated and coated with neutral petrolatum-based compounds and inert fillers. All tapes are chemically inert and do not polymerize or oxidize. Therefore it retains water resistance and dielectric properties over an indefinite period. It is free of chemical impurities.

PetroWrap® Anti-Corrosion Tape Systems provides a wider temperature range of protection than any other product of its type in the market place. -40°C - +85°C allows for maximum performance and integrity at extremely low and high temperatures.

Tape Product	Order Code	Width	Length	Rolls/Box
PetroWrap® Tape 2"	A06-PW50-036	50 mm (2")	10 m (32.8 ft)	36
PetroWrap [®] Tape 3"	A06-PW75-024	75 mm (3")	10 m (32.8 ft)	24
PetroWrap [®] Tape 4"	A06-PW100-018	100 mm (4")	10 m (32.8 ft)	18
PetroWrap [®] Tape 6"	A06-PW150-012	150 mm (6")	10 m (32.8 ft)	12
PetroWrap® Tape 8"	A06-PW200-008	200 mm (8")	10 m (32.8 ft)	6

PetroWrap® Mastics, Primer Pastes, OverWraps

For Maximum Corrosion Protection use the following products:

PetroWrap® Mastic (Filler)

- Press-on putty for filling voids and pockets on surfaces to be wrapped Idea for flanges and valves
- Available in 500 g blocks 36 blocks/case Order Code A06-PWM-036
- Available in 2.5 Kg blocks 6 blocks/case Order Code A06-PWM-006

PetroWrap[®] Primer Paste

- Primer for surface preparation
- Displaces moisture
- Available in 4 x 4kg containers Order Code A06-PWP-004
- Available in 6 x 2kg containers Order Code A06-PWP-006

PetroWrap[®] OverWrap Tape

- Polyethylene tape coated on one side with natural rubber-based pressure-sensitive adhesive
- Adheres to Petrolatum Tapes to provide an attractive finish for Petrolatum Tape Products
- Available in 50mm widths: 36 x 30m rolls per box Order Code A06-PWO50-036
- Available in 100mm widths: 18 x 30m rolls per box Order Code A06-PWO100-018

Can be applied on wire brushed surfaces	 Repels water, salt, alkalis, and acids 	Non-toxic and non-polluting
 Withstands temperatures -40°C to 85°C 	Will not crack, peel, or harden	Protects new or corroded surfaces

Tape and Paste Application Instructions

- <u>Priming:</u> All surfaces should be evenly coated with **PetroWrap[®] Primer Paste** prior to application of **PetroWrap[®] Tape.**
- <u>Overwrapping:</u> Pipes wrapped with **PetroWrap®** Tape may be over-wrapped with **PetroWrap®** OverWrap Tape for extra mechanical protection and increase electrical resistance.
- <u>Finishing:</u> While applying the **PetroWrap®** Tape, smooth the surface of the tape by hand to eliminate air bubbles. Insure intimate contact with the substrate and seal laps.
- <u>Overlapping:</u> A 55% overlap is generally recommended, however, a minimum overlap of 1" may be used on pipe diameters up to 6" and a 2" overlap on larger diameters.








Primer and Filler Instructions

- · Remove all contaminants such as dirt, oil, scale, and excessive moisture
- Brush *PetroWrap[®]* Primer Paste evenly over surface to displace remaining moisture and ensure proper adhesion
- Press PetroWrap[®] Mastic Filler (B) into surface irregularities to eliminate air pockets
- Wrap *PetroWrap[®]* Tape(C) spirally around prepared surface using even tension. An overlap of 50% is
 recommended to assure total protection.
- Where necessary on top of the *PetroWrap[®]* Tape wrap *PetroWrap[®]* OverWrap Tape (D)



Manufacturer: Innovative Manufacturing Division 861 Derwent Way Delta, B.C, Canada, V3M 5R4

Master Distributor: VapCor Inc. Canada 530 Eastchester Ave. St. Catharines, Ontario, Canada, L2M 7P3, Ph# 905-346-2638 Ph# 866-642-1311, Fax# 905-682-3300 Solutions@Vapcor.com www.vapcor.com USA 3909 Witmer Rd. Unit 1029 Niagara Falls, NY, 14305, Seattle, Washington, Miami, Florida Ph# 866-642-1311 Solutions@vapcor.com

The details of our products are given completely free of undertaking. Since their application lies outside our control, we cannot accept any liability for the results. User shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. All rights reserved